




## LKX1310LP




### Standard equipment:

- 3.700.0030 - M22 Industrial Gun



- 3.701.0015 Industrial Spray Lance



- 4.618.0143 10M Double Steel Braided Hose



- 3.103.0003 Nozzle



### Equipped with:

- Four Pole Electric Motor with Thermal Protection
- Three Ceramic Coated Pistons
- Brass Crankshaft Pump Head with Built-In By-Pass Valve
- Low Voltage and Delayed Total Stop
- Suction and Delivery Stainless Steel Valves
- Vertical Burner with High Thermal Efficiency Steel Coil
- Adjustable Temperature Thermostat
- Detergent Tank for Indirect Suction
- Low Fuel Safety Cut Out



### Optional:

- 6.602.0051 Industrial Foaming Lance

(\* Requires  
0.999.1015  
Coupling)



- 0.999.0126 Turbo Lance



- 0.999.0100 20M Dbl Steel Braided Hose

- 0.999.0130 30M Dbl Steel Braided Hose

(\* Requires  
3.100.0043  
Coupling)



\* More Options Available

LKX1310LP	
Code	8.621.1007
Standard Operating Pressure	1800 PSI
Maximum Water Volume	11 Litres/Minute, 660 Litres/Hour
Motor Specifications	240V (15 Amp), 1Ph, 3.0KW (4.0HP)
Pump Type/RPM	CL4/1450
Max. Water Outlet Temperature	140 °C
Dimension/Weight	70x110x110cm/100 Kg