

THERMIC3500

CRANKSHAFT



Equipped with:

- Honda GX390 Unleaded Motor with **3 Year Warranty**
- Heavy Duty Italian Linear Pump with Brass Head
- Adjustable Pressure Unloading Valve
- 2:1 Reduction gearbox
- By-Pass Thermal Dump Valve
- Low Pressure Detergent Pickup
- Stainless Steel Trolley
- Non-Marking High Pressure Hose 15m (Grey)
- Wide (25cm) Pneumatic Tyres

Standard equipment:

- 0.999.4001 Industrial Gun



- 0.999.4002 Industrial Steel Spray Lance



- 0.999.0117 15M Steel Braided HP Hose



- 0.999.1003 QR Nozzles



Optional:

- 6.602.0051 Industrial Foaming Lance

(* Requires
0.999.0104
Coupling)



- 0.999.0129 Turbo Head



- 0.100.0006 20" Whirl-A-Way



* More Options Available

THERMIC3500	
Code	8.601.0022
Max Operating Pressure	3500 PSI
Maximum Water Volume	15 Litres/Minute, 900 Litres/Hour
Motor Specifications	13HP Honda Unleaded Petrol - 4 Stroke
Pump Type/RPM	Crankshaft / 1700
Max. Water Inlet Temperature	40 °C
Dimension/Weight	85x70x65cm/75 Kg