

LAVOR4015HE

CRANKSHAFT



Standard equipment:

- 0.999.4001 Industrial Gun



- 0.999.4002 Industrial Steel Spray Lance



- 0.999.0117 15M Steel Braided HP Hose



- 0.999.1002 QR Nozzles



Optional:

- 0.999.0140 Turbo Head



- 0.100.0006 20" Whirl-A-Way



* More Options Available



Equipped with:

- Honda GX390 Unleaded Motor with **3 Year Warranty and Keystart**
- Heavy Duty Italian Linear Pump with Brass Head
- Marine Sealed Battery
- Adjustable Pressure Unloading Valve
- By-Pass Thermal Dump Valve
- Low Pressure Detergent Pickup
- Powder Coated Heavy Duty Steel Trolley with Centre Balanced Lift Hook
- Non-Marking High Pressure Hose 15m (Grey)
- Wide (33cm) Pneumatic Tyres

LAVOR4015HE	
Code	8.601.0021
Max Operating Pressure	4000 PSI
Maximum Water Volume	15 Litres/Minute, 900 Litres/Hour
Motor Specifications	13HP Honda Unleaded Petrol - 4 Stroke
Pump Type/RPM	Crankshaft / 3400
Max. Water Outlet Temperature	100 °C
Dimension/Weight	132x91x140cm/240 Kg