

LAVOR

PROFESSIONAL

Hot Water Electric Pressure Washer

HYPER L

1450 RPM

CRANKSHAFT



BRASS HEAD



Standard equipment:

- 3.700.0029 - AL55 Pressure Adjustable Industrial Gun



- 3.708.0001 Industrial Spray Lance



- 4.618.0143 10M Double Steel Braided Hose



- 3.103.0003 Nozzle




Optional:

- 6.602.0051 Industrial Foaming Lance
(* Requires 0.999.1015 Coupling)



- 0.999.0126 Turbo Lance



- 0.999.0100 20M Dbl Steel Braided Hose
- 0.999.0130 30M Dbl Steel Braided Hose

(* Requires 3.100.0043 Coupling)



* More Options Available

Equipped with:

- Four Pole Electric Motor with Thermal Protection and Water Cooling (Cooling on 415v model only)
- Three Coated Pistons
- Crankshaft Pump and Brass Pump Head with Built Valve
- Integrated Elastic Joint
- Low Voltage and Delayed Total Stop
- Equipped with Pressure on Gun
- Vertical Burner with High Thermal Efficiency
- Adjustable Temperature Thermostat
- Detergent Tank for Built In High Pressure Application
- **Stainless Steel Heating Coil with 3 Year Warranty**

T.S
Total Stop 24V

	HYPER L 1211 (240v)	HYPER L 2015 (415v)
Code	8.621.0994	8.621.1041
Standard Operating Pressure	1800 PSI	3000 PSI
Maximum Water Volume	11 Litres/Minute, 660 Litres/Hour	15 Litres/Minute, 900 Litres/Hour
Motor Specifications	240V (15 Amp), 1Ph, 3.0KW (4.0HP)	415V (20 Amp), 3Ph, 7.3KW (9.7HP)
Pump Type/RPM	CL4/1450	CL5/1450
Max. Water Outlet Temperature	140 °C	140 °C
Dimension/Weight	70x110x110cm/109 Kg	70x110x110cm/135 Kg