



WALLMOUNT



CRANKSHAFT



Standard equipment:

- 3.700.0030 - AL55 Industrial Gun



- 3.708.0001 Industrial Spray Lance



- 4.618.0143 10M Double Steel Braided Hose



- 3.103.0003 Nozzle



T.S. Total Stop

Equipped with:

- Four Pole Electric Motor with Thermal Protection and Water Cooling (Water Cooling on 415v only)
- Three Ceramic Coated Pistons
- Brass Crankshaft Pump Head with Built-In By-Pass Valve
- Integrated Elastic Motor/Pump Coupling for Shock Absorption
- Low Voltage and Delayed Total Stop
- Suction and Delivery Stainless Steel Valves
- Glycerine Pressure Gauge
- Stainless Steel Cabinet and Chassis
- Zero Line/Hose Pressure Unloader System

Optional:

- 6.602.0051 Industrial Foaming Lance
(* Requires 0.999.1015 Coupling)



- 0.999.0170 360 Degree Ceiling Boom
(Differing Sizes Available)



- Hose reels, differing sizes and types.
Ask for Options.



* More Options Available

| | WALLMOUNT 1211 (240v) | WALLMOUNT 2015 (415v) |
|-------------------------------|-------------------------------------|-----------------------------------|
| Code | 8.626.0448 | 8.626.0044 |
| Standard Operating Pressure | 1800 PSI | 3000 PSI |
| Maximum Water Volume | 11.6 Litres/Minute, 696 Litres/Hour | 15 Litres/Minute, 900 Litres/Hour |
| Motor Specifications | 240V (15 Amp), 1Ph, 3.0KW (4.0HP) | 415V (20 Amp), 3Ph, 7.3KW (9.7HP) |
| Pump Type/RPM | CL5/1450 | CL5/1450 |
| Max. Water Outlet Temperature | 40 °C | 40 °C |
| Dimension/Weight | 75x50x31cm/42 Kg | 75x50x31cm/46 Kg |